

Planetary Data System

PDS4 Product Search and Query Models

J.S. Hughes, J.H. Padams, G.A. Hollins, and S.H. Hardman

Jet Propulsion Laboratory

California Institute of Technology

4th Planetary Data Workshop

June 18–20, 2019

Flagstaff, Arizona

Planetary Data Archives
Support Services, and Tools I
Wednesday, June,19 2019
9:45 a.m HCCC Humphreys



Search Goals

Improved integration across nodes and across agencies

- Pass search parameters to the node search engines (e.g., two/n-tiered search).
- International data sets integrated with PDS search results.

Better navigation and support for mission and other "virtual" views

- resources that can be browsed / linked-to easily
- PDS mission support pages registered in the PDS search infrastructure.
- Facet-based navigation to drive specific views.

Development Approach


- Build the software system based on generic common software and common protocols for accessing that software.
 - PDS Registry along its access APIs is the main component.
 - PDS Registry based on Apache Solr provides support for high performance facet-based search.
- Utilize the PDS4 data model for data object definitions and to configure the software where appropriate.
 - The model defines the key context objects (i.e., Investigation, Instrument, Collection, Observational Data, etc.).

Registry

- This service is a deployable component that accepts queries for data and returns a set of matching results.
- Provides the public interface (REST-based API over HTTP) to the metadata contained in the federated instances of the Registry Service.
- Generation of search indices from registry metadata supports multiple query formats and is tailor-able for customized search interfaces.



Search Architecture



Search Protocol

- Common PDS-based parameters
 - Includes identifier, instrument, investigation, etc.
 - Includes mapping from PDS3 to PDS4.
- Supports simple and advanced syntaxes
 - Simple syntax closely follows HTTP.
 - Advanced syntax closely follows Apache Lucene/Solr.
- Supports multiple result set formats
 - Default format available in XML and JSON.
 - Initial support for VOTable.
- All the above detailed in the PDS Search Protocol [1] and PDAP Search Protocol [2] documents.
- [1] https://pds.nasa.gov/services/pds4_pds_search_protocol.pdf
- [2] https://pds.nasa.gov/services/pds4_pdap_search_protocol.pdf

Service Configuration

- Much of the functionality provided by the Registry and Search is achieved through manual configuration.
 - Defining search fields, facets, etc. in Apache Solr.
 - Mapping XPath to human-readable searchable fields
- Wouldn't it be great if this could be automatically configured directly from the PDS Information Model?
 - Query models appear to be the answer.

What is the purpose of a Query Model?

- A query model identifies attributes that are useful for search.
 - PDS4 product labels contain information that is useful for locating data products in the archive.
- A query model is used to configure system functions
 - Harvester extracts the value of the identified attributes
 - Search API to allow searching these values

Jet Propulsion Laboratory California Institute of Technology Pasadena, California

Product Label Template

```
Identification Area
  Logical Identifier
  Version Id
Observation Area
  Time Coordinates
                               Discipline Area
  Primary Result Summary
                               Mission Area
  Investigation_Area
  Observing_System
  Target_Identification
Reference_List
  Internal Reference
  External_Reference
File_Area_Observational
  File
     Header
     Array 2D Image
```

Pasadena, California

Some Useful Search Attributes


Target: Product Collections(Mission Science Data Collections)

- collection_type=Data
- type=Mission
- product_class=Product_Collection
- purpose=Science

Search Parameters for Mission Science Data Collections		
Candidate attribute for search	Faceted	Text- or
	Search	Field-
		Search
Product_Collection.Collection.collection_type=Data	Yes	Yes
Investigation_Area.type=Mission	Yes	Yes
Identification_Area.product_class=Product_Collection	Yes	Yes
Primary_Result_Summary.purpose=Science	Yes	Yes
Time_Coordinates.start_date_time		Yes
Time_Coordinates.stop_date_time		Yes
Target_Identification.name		Yes
Target_Identification.type	Yes	Yes
Investigation_Area.name		Yes
Observing_System.name		Yes
Observing_System_Component.name		Yes
Observing_System_Component.type	Yes	Yes
(type=Instrument)		
Primary_Result_Summary.processing_level	Yes	Yes
Science_Facets.domain	Yes	Yes
Science_Facets.wavelength_range	Yes	Yes
Science_Facets.discipline_name	Yes	Yes
Collection.description		Yes
Product_Context.Instrument.type	Yes	Yes
Identification_Area.logical_identifier		Yes
Identification_Area.version_id		Yes
Science_Facets.facet1	Yes	Yes
Science_Facets.facet2	Yes	Yes
Primary_Result_Summary.description		Yes
Target_Identification.description		Yes
Identification_Area.title		Yes
system.archive_status	Yes	Yes
Citation_Information.keyword		Yes
Citation_Information.description		Yes



Search Architecture





Product Label Template

```
Identification Area
  Logical Identifier
  Version Id
Observation_Area
                               Discipline_Area
  Time Coordinates
  Primary Result Summary
                               Mission Area
  Investigation_Area
  Observing_System
  Target_Identification
Reference List
  Internal Reference
  External_Reference
File_Area_Observational
  File
     Header
     Array 2D Image
```

How are Query Models populated?

```
<Ingest LDD</pre>
 <name>Cartography</name>
        <DD Attribute>
          <name>map projection name</name>
          <version id>1.0/version id>
          <local identifier>map projection name</local identifier>
          <nillable flag>false</nillable flag>
          <query_model_name>Cart QM 1<query_model_name>
          <query model name>Cart QM 2<query model name>
          <submitter name>Elizabeth D. Rye</submitter name>
          <definition>The map projection name attribute provides ... </definition>
          <DD Value Domain>
```

Thank You

Jet Propulsion Laboratory California Institute of Technology Pasadena, California

Data Flow

